

BLADE MATE



Bottom Line Benefits

- The hydraulic stinger arm eliminates the need for lifting the trailer when opening and closing.
 - The two steering cylinders are located under the beam, achieving the same amount of force when turning left or right.
 - The trapezoidal beam reduces twisting and deflection.
 - The neck is detachable so a standard or flip neck can be used.
 - A beam extension can be added when the neck is deduced.
 - The second beam lock is at the front of the third beam so either beam can be pulled out first.
 - The movable bunk offers versatility between blade manufacturers and types.
 - The rollers offer ease in extending and reduces friction between moving parts.
 - The axles are mounted on a turntable for more accurate steering.
 - The steering locks into place when going down the road or in reverse.
- The clamps are located on bumper for adjustable ground clearance.

*Photos may show some optional equipment



Standard Specs

- Over all open length 129'-5" (144'-5" with bumper)
- Over all closed length 53'
- 10'-1" axle spacing
- 49" loaded rear height
- 54" height on neck load platform (with 49" 5th wheel height truck)
- 2 blade supports
- Weight of trailer without tacos and bunk is 25,200 pounds
- 13 HP Honda power unit to control steering and stinger
- Wired remote with 50' cable
- Bunk to fit on all three beams
- 37 degrees of steering each direction
- 15' extending bumper

877-283-4852 Toll Free
1086 S. 3rd St - Manchester, Iowa

www.xlspecializedtrailer.com

